

Advanced Wrist Blood Pressure Monitor



Specifications

Model Number	WBP3		
Power Supply	Ba ery powered mode: 2*AAA ba eries (3V DC)		
Display Mode	Digital LCD V.A. 45mm x 33mm	SYSTOLIC ————————————————————————————————————	sī,
Measurement mode	Oscillographic tes ng mode	DIASTOLIC ————————————————————————————————————	<u> </u>
Measurement range	Rated cuff pressure: 0mmHg ~ 299mmHg (0kPa ~ 39.9kPa)	PULSE RATE——	PUL
	Measurement pressure:	SET BUTTON ——	+
	SYS: 60mmHg ~ 230mmHg (8.0kPa ~ 30.7kPa)		
	DIA: 40mmHg ~ 130mmHg (5.3kPa ~ 17.3kPa)		
	Pulse value: (40-199) beat/minute		
Accuracy	Pressure: 5°C-40°C within±3mmHg (0.4kPa) Pulse value: ±5%		
Normal working condition	A temperature range of: +5°C to +40°C A rela ve humidity range of 15%		
	to 90%, non-condensing, but not requiring a water vapour par al pressure		
	greater than 50 hPa An atmospheric pressure range of: 700 l	hPa to 1060 hPa	
Storage & transportation	Temperature: -20°C to +60°C A rela ve humidity range of ≤ 93%,		
condition	non-condensing, at a water vapour pressure up to 50hPa		
Measurement perimeter	About 13.5cm-21.5cm		
of the wrist			
Dimensions & Weight	Approx. $86 \times 66 \times 22$ mm (Excluding the cuff) - Approx. 100g (Excluding the ba		eries
Attachment	2×AAA ba eries, User manual, Quick start guide		

Structure

GRADE

LCD DISPLAY

MEMORY BUTTON START/STOP BUTTON

