



Features

- ✓ Flexible tip
- ✓ Rapid measurement - 10 seconds
- ✓ Waterproof
- ✓ Fever alarm
- ✓ Break resistant
- ✓ Auto-shut off



Specifications

Model number	DMT-4336
Measuring range	32.0°C ~ 42.9°C (90.0°F ~ 109.9°F) (°C/°F chosen by manufacturer)
Accuracy	±0.1°C(±0.2°F) during 35.5°C ~ 42.0°C(95.9°F ~ 107.6°F) at 18°C ~ 28°C (64.4°F ~ 82.4°F) ambient operating range ±0.2°C (±0.4°F) for other measuring and ambient operating range
Display	Liquid crystal display, 3 1/2 digits
Memory	For storing the last measured value
Battery	One 1.5V DC. button battery (size LR41 or SR41, UCC 392)
Battery life	Approx. 200 hours of continuous operation or 1 year with 3 measurements per day
Dimensions	13.1cm x 2.0cm x 1.2cm (L x W x H)
Weight	Approx. 10 grams including battery
Expected service life	Three years
Ambient operating range	Temperature: 5°C ~ 40°C (41°F ~ 104°F) Relative humidity: 15% ~ 95%RH Atmospheric Pressure : 700hPa ~ 1060hPa
Storage and transportation condition	Temperature: -20°C ~ 55°C (-4°F ~ 131°F) Relative humidity: 15% ~ 95%RH Atmospheric Pressure : 700hPa ~ 1060hPa
Ingress protection rating	IP 27
Classification	Type BF

Structure

