

Features

- ✓ Universal Cuff (22-42cm) & XL Cuff (40-52cm) Included
- ✓ Clinically Validated
- ✓ Large Display
- ✓ Average Readings
- ✓ Irregular Pulse Rate Detection
- ✓ 2 User x 199 Memory Storage, with Date and Time
- ✓ Automatic Cuff Wrap Detection
- ✓ Excessive Body Motion Detection
- ✓ Pulse Rate Display



Specifications

Model Number	TMB-2287-K
External Dimensions	Approx. 140mm × 130mm × 55.6mm
Display Mode	Digital LCD V.A. 60.5mm × 92.5mm
Weight	Approx. 265g
Measurement mode	Oscillographic testing mode
Mode of operation	Continuous operation
Measurement range	Rated cuff pressure: 0 mmHg ~ 299 mmHg Measurement pressure: SYS: 60 mmHg ~ 230 mmHg DIA: 40 mmHg ~ 130 mmHg Pulse value: (40 - 199) beat/minute
Accuracy	Pressure: 5°C ~ 40°C within ±3 mmHg. Pulse value: ±5%
Normal working condition	A temperature range of: +5°C to +40°C A relative humidity range of 15% to 90%, non-condensing, but not requiring a water vapour partial pressure greater than 50 hPa An atmospheric pressure range of: 700 hPa to 1060 hPa
Storage and transportation condition	Temperature: -20°C to +60°C A relative humidity range of ≤ 93%, non-condensing, at a water vapour pressure up to 50 hPa An atmospheric pressure range of 500 hPa to 1060 hPa
Degree of protection	Type BF applied part
Protection against ingress of water	IP21
Types of use	Multiple patient multiple use

Structure

